



## ST 2.36 C5

PORTABLE POWER

WATERPUMP Range AQUALINE INTENS

### PRODUCT ADVANTAGES

HONDA Professional Engine  
Automatic priming  
Offers accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

### Range AQUALINE INTENS

Designed for water with low solid content.



## ST 2.36 C5

### GENERAL SPECIFICATIONS

Range	AQUALINE INTENS
Type liquid	Clear water with little sediment pump
Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (L/min)	600
Outflow maximum (m3/h)	36
Lifting height (m)	29
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Oui
Fuel	Petrol
Tank (L)	2
75% cons. (l/h)	1
75% Autonomy (h)	2
Sound power level guaranteed LwA dB(A)	103
Acoustic pressure level @1m in dB(A)	87
Acoustic pressure level @7m in dB(A)	72

### ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX120_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	118
Oil system capacity including filters (l)	0.6

### DIMENSIONS AND WEIGHT

Length (cm)	46.8
Width (cm)	36.2
Height (cm)	38
Dry Weight (kg)	23

### PACKAGING

Packaging type	Box
Length (cm)	48.5
Width (cm)	38.5
Height (cm)	40
Weight (kg)	24.5
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	133
weight of the packaged Pallet (kg)	304

### ACCESSORIES SUPPLIED

Inlet filter  
Circlips  
Screw-on connectors  
User and maintenance manual

### OPTIONS

- RBH1** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
- RBH0-5** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
- RHO** Cover for SDMO 's generating sets, welding sets and water pumps
- R11** Piping kit for 2 water pumps made up of 5m suction + 25m lift
- R13** Rapid connections kit for 2 water pumps