



ST 3.60 C5

PORTABLE POWER

WATERPUMP Range AQUALINE INTENS

PRODUCT ADVANTAGES

HONDA Professional Engine
Automatic priming
Offers accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range AQUALINE INTENS

Designed for water with low solid content.



ST 3.60 C5

GENERAL SPECIFICATIONS

Range	AQUALINE INTENS
Type liquid	Clear water with little sediment pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	900
Outflow maximum (m3/h)	54
Lifting height (m)	26
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Oui
Fuel	Petrol
Tank (L)	3.1
75% cons. (l/h)	0.9
75% Autonomy (h)	3.4
Sound power level guaranteed LwA dB(A)	105
Acoustic pressure level @1m in dB(A)	90
Acoustic pressure level @7m in dB(A)	75

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX160_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (l)	0.6

DIMENSIONS AND WEIGHT

Length (cm)	50.5
Width (cm)	41.4
Height (cm)	44.8
Dry Weight (kg)	29

PACKAGING

Packaging type	Box
Length (cm)	52
Width (cm)	42.5
Height (cm)	46.5
Weight (kg)	32
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	153
weight of the packaged Pallet (kg)	394

ACCESSORIES SUPPLIED

Inlet filter
Circlips
Screw-on connectors
User and maintenance manual

OPTIONS

- RBH1** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
- RBH0-5** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
- RHO** Cover for SDMO 's generating sets, welding sets and water pumps
- R12** Piping kit for 3 water pumps made up of 5 m suction + 25 m lift
- R14** Rapid connections kit for 3 water pumps