

Angle Grinder

GA5040C

1 400 W • 125 mm • 11 000 min⁻¹

Effective tool with anti-restart function for cutting and grinding

A small 1,400W angle grinder with a 125 mm wheel for demanding applications. Integrated SJS2 anti-vibration technology and AVT anti-vibration side grip. Tool-less wheel replacement and anti-restart function.



Technical specifications

Continuous Input Power	1400 W
No load speed	2 800 – 11 000 min ⁻¹
Power Supply Cord	2,5 m
Spindle Thread	M14
Grinding Disc Diameter	125 mm
Bore (B)	22,23 mm
Anti-Restart Function (NVR Switch)	✓
Sound Power Level (L _{WA})	86 dB(A)
Sound Pressure Level (L _{pA})	97 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	5,5 m/s ²
Weight Without Cable (EPTA)	2,5 - 3,6 kg
Product Dimensions (L x W x H):	303 x 140 x 116 mm

User benefits

- Double insulated
- Rubberised soft grip for more comfort and control
- Soft grip for increased operator comfort
- Makita's patented Super Joint System protects the gearbox and operator from kickback.
- Super Joint System (SJS) mechanical clutch system helps minimise motor and gear damage
- Electronic current limiter helps protect the motor from overload
- Anti-restart function prevents accidental start-up even if the tool is plugged to power source with the switch ON
- Constant speed control minimises reduction in rotation speed under load

EAN 0088381629140

Link to product - www.makita.com



Related products

■ Optional AC

153489-2
Grip complete 125 mm



192227-7
Super Flange 115 - 230 mm, M14



■ Other

User manual

Parts drawing