RUNG LADDERS www.hymer-alu.de

## A12 > Ver. Lad > Wit > Ste pos bef > Size > Soli > Set > Lov Note: Hinges must be kept clean and regularly lubricated.

## 4142 Telescopic ladder

- > Versatile for use as leaning or freestanding ladder.
- > Ladder extendable in 250 mm steps.
- > With foldable stabilisers for higher stability (complies with EN 131-1).
- Steel hinge with locking clamp easy to use. In the freestanding ladder position, the hinge must be released by hand before folding the ladder.
- > Size 4×6 with hinged joint\* as 8142 (see on page 21).
- > Solid locking devices with steel core for height adjustment.
- > Set up in stairway mode possible.
- › Low space requirements for storage and transport.















Number of rungs	4×4	4×5	4×6
Stile (approx. mm)	60	60	60
Number of rungs at max. extension	14	18	22
Length leaning ladder (approx. m)	2.35 – 4.02	2.90 – 5.14	3.46 – 6.26
Standing height freestanding ladder (approx. m)	1.26	1.80	2.35
Reach height freestanding ladder (approx. m)	3.26	3.80	4.35
Standing height leaning ladder (approx. m)	3.00	4.10	5.20
Reach height leaning ladder (approx. m)	5.00	6.10	7.20
Vertical height freestanding ladder (approx. m)	1.15 – 1.95	1.40 – 2.49	1.70 – 3.03
Width as freestanding ladder top/bottom (approx. mm)	355/830	355/945	355/1,055
Folded L×W×H (approx. m)	1.20×0.60×0.20	1.50×0.70×0.20	1.80×0.75×0.20
Base width retracted/extended (approx. m)	0.87/1.36	1.03/1.72	1.20/2.01
Weight (approx. kg)	13.2	16.2	19.0
Order no.	414216	414220	414224

For an explanation of standing/reach height see on page 5.

## **Recommended accessories:**





for rung ladders



Tool bag



Foot extension





Set of swivelling foot pikes

Fixed castor set

## Spare part:

ladder step

Spare parts set rung covers, order no. 0054047, see on page 134.