

PROGUARD DIRT TRAP MAT



Product Code	Pricing Unit	Colour	Dimensions	Thickness	Pack Quantity	Pallet Quantity
PSM2	EACH	CLEAR	610mm X 762mm	30 Layers	4	40

Product Description:

Proguard Dirt Trap Mats are the first ever contamination control product containing renewable plant-based materials, providing an environmentally friendly alternative for socially responsible organizations.

Proguard dirt trap mats are tacky plastic sheets that provide containment of dust and dirt during fit out and refurbishment work. Each tacky mat contains 30 peel-away layers coated with a pressure sensitive adhesive. The sheets help to protect from dirt and dust being transferred to non-working, clean areas, saving you clean-up time at the end of the project. Once the top layer becomes soiled this can be removed to leave a clean layer.

Each layer of the mat is fully coated with a particle grabbing adhesive and constructed of low-density polyethylene film. A low-profile numbered tab indicates the number of remaining layers and ensures one-layer-at-a-time removal. The tack mats will remove dirt and debris from foot and wheeled traffic. 20% of the material comes from renewable plant-based material that reduces CO2 emissions.

These mats are designed for use with our Proguard Dirt Trap Mat Frames (PSMF1) or for use as stand-alone mats. Once the 30-layer mat on the Proguard Frame has been used, replace with a new Proguard mat (PSM2)

Benefits:

- Heavy duty for industrial usage
- Environmentally friendly – Contains GMO free, renewable, plant-based Cardia BioHybrid™ material that reduces CO2 emissions.
- Image Enhancer – Improves your corporate image by lowering your carbon footprint.
- Captures 99% of all foot borne contaminants.
- Anti-microbial Adhesive
- Low profile
- Easy to install.
- Designed for use with Proguard PSMF1 Frame
- Prevent dirt and dust transfer into clean areas.
- Recyclable

Limitations:

- Obviously, adhesion will be reduced on dusty surfaces. Vacuuming prior to use is recommended.
- It is the user's responsibility to determine suitability for use. If in doubt, contact technical services for advice.

Application:

Ensure the floor to which the trap mat is to be applied is clean, dust free and dry. Remove the peel able layer on the underside. This will leave a tacky surface – fix this to the floor between the clean and working areas or onto the Proguard PSMF1 Frame. Ensure that the trap mat is stuck firmly in place.

Peel off the top layer which will leave a tacky surface which will remove dirt and debris from foot and wheeled traffic.