



BRAKED
CASTORS



OPTIONAL
POLE HOLDERS



INTEGRATED
TIPPING SYSTEM

TECHNICAL SPECIFICATIONS

PERFORMANCE & MOTOR		PHYSICAL SPECIFICATIONS		FEATURES & BUILD	
Engine Type	Loncin G200F	Drum Size	90 Litres	Tipping Drum	Yes
Pull Start	Standard	Drum Capacity	60 Litres	Drain Hose	Yes
Keystart	Optional	Dimensions	1170 x 600 x 920mm	Removable Drum	Yes, QUIKLIFT System
Max RPM	2800	Empty Weight	98Kg	Float Valve System	Yes, Integral
Suction	420mBar	Full Weight	158Kg	Float Valve for Wet Use	Yes
Airflow	180m³/hr	Inlet	50mm Side cyclone type	Dry Option	Yes
Blower Function	Yes	Locking Wheels	Front	Pole Holder	50mm and 40mm optional
		Front Wheels	100mm Braked	Locking Wheels	Front
		Rear Wheels	260mm Puncture Proof	EasyReach Compatible	Yes

AVAILABLE HOSE OPTIONS	
50mm Superflex Hose, 7.5m length with cuff & drum connector	PV-ACC-001
40mm Superflex Hose, 7.5m length with cuff & drum connector	PV-ACC-002
60mm Pole Holder Set for 3× 50mm Poles	PV-ACC-003
50mm Pole Holder Set for 3× 40mm Poles	PV-ACC-004