



Tridonic driver suitable for use with LED Panels up to 40W, offering excellent reliability and performance.








Specification

- Voltage:** 220-240V
- Output Voltage range:** 27-39V
- Output Current (constant):** 900mA
- Maximum Wattage:** 39W
- Input Current:** 0.205A
- Power Factor:** >0.9
- Ta:** -20°C - 50°C
- Life Expectancy:** 50,000 Hours
- Guarantee:** 5 Year guarantee
- IP Rating:** IP20
- Material:** Polycarbonate, white
- Extra Info:**



Over-temperature protection. Overload protection.
 Short circuit protection. No-load protection
 Complies to the following standards: EN55015, EN 60598-1, EN 61000-3-2, EN 61000-3-3, EN 61347-1, EN 61347-2-13 & EN 61547. Tridonic reference: 8750051.
 Supplied with 50cm Male 2.1mm DC Connector.

Automatic Circuit Breaker Type	C10	C13	C16	C20	B10	B13	B16	B20
Installation Ø	1.5mm ²	1.5mm ²	1.5mm ²	2.5mm ²	1.5mm ²	1.5mm ²	1.5mm ²	2.5mm ²
QTY	33	50	66	83	25	38	50	58

MODEL	SUITABLE PRODUCTS	DIMENSIONS (L x W x D mm)
LEDP40-DRIVERT	LED PANELS	130 x 68 x 31