



(Image shown LEDPE40-64)

The LED LITEMOD 40w panel provides a straight forward replacement for traditional fluorescent fittings. The LITEMOD is engineered to deliver exceptional lighting performance and impressive energy savings.




Specification

Voltage: 220-240V
Wattage: 40W
LED: 192pcs of 2835 SMD LED
Lumen Output: 3200-3400lm
Life Expectancy: 50,000 hours
Guarantee: Two year
IP Rating: IP40
Beam Angle: 160°
Material: 9mm Aluminium frame & 3mm LGP

CRI: >80
Fire Performance: TP(b)
Working Temp.: -20 C - 40 C

Extra Info: Flicker free driver. Easy 'plug & play' emergency solution using EMLEDKITND-1 or EMLEDKIT-MP. Surface Mounting Kit (LEDP-SMKW) or Recessed Mounting Kit available (LEDP-RMKW), both in white finish.



MODEL	WATTAGE	COLOUR	COLOUR TEMPERATURE	LUMEN OUTPUT	DIMENSIONS (L x W x D mm)
LEDPE40-41	40W	Chrome	4100K COOL WHITE	3200lm	595 x 595 x 9mm
LEDPE40-64	40W	Chrome	6400K DAYLIGHT	3400lm	595 x 595 x 9mm