

Empty body non-corrosive fittings suitable for use with LED tubes. Our unique 'dual-config' system means that 'wired both ends' or 'wired one end' can be accommodated with a quick tool-less conversion.



1 x 18W
1 x 36W
1 x 58W
1 x 70W






Specification

Voltage: 240V / 50Hz
LED Tube: 2 ft / 4 ft / 5ft / 6ft
Guarantee: 1 year
IP Rating: IP65
Material:

Base: High impact resistant ABS
Diffuser: Polycarbonate clear

Working Temp: -20°C - 60°C
Extra Info:

No ballast., c/w plastic clips - stainless steel available separately, standards: F mark, CE, BS EN 61140; BS EN 60598:2008. UV resistant diffuser.
Wired Live and neutral to one end as standard.
Simply remove the fuse on the circuits to convert to 'wired both ends.'



MODEL	SIZE	LED TUBE TO MATCH	DIMENSIONS (L x W x D mm)
WF18B-1	2 FT SINGLE	T8LED210-40/60	665 x 98 x 102mm
WF36B-2	4 FT SINGLE	T8LED418-40/60	1270 x 98 x 102mm
WF58B-1	5 FT SINGLE	T8LED522-40/60	1586 x 98 x 102mm
WF70B-1	6 FT SINGLE	T8LED626-40/60	1880 x 98 x 102mm