





5W LED Emergency Twin Spot with a lightweight polycarbonate body for easy mounting and installation. Three LED indicators provide visual confirmation of the status of the fitting.



## Specification

<b>Voltage:</b>	220-240V 50/60Hz
<b>Power Consumption:</b>	5.2W
<b>LED:</b>	Two x 40 pcs of Ø 5
<b>Lumen Output:</b>	416lm
<b>Power Factor:</b>	0.91
<b>Colour Temp.:</b>	6000K-7000K
<b>Emg. Duration:</b>	Three hours
<b>Guarantee:</b>	One year
<b>IP Rating:</b>	IP20
<b>Life Expectancy:</b>	40,000 Hours
<b>Material:</b>	Polycarbonate
<b>Battery:</b>	Ni-Cd D3.6V 4500mAH
<b>Charging Time:</b>	24 hours
<b>Working Temp:</b>	0°C - 40°C
<b>Extra Info:</b>	3V Deep discharge protection. 4.3V Overcharge protection. Weight: 1143g. Ø20mm Cable entry hole size. Class one safety classification. Wall installation. CE certified.



MODEL	WATTAGE	LUMEN OUTPUT (LM)	DIMENSIONS (L x W x D mm)
LF292E	5.2W	416LM	308.5 x 280 x 55.5