

STELLAR

3CCT FIRE RATED DOWNLIGHT

Stellar is an ultra-slim downlight that delivers an extensive list of cutting edge features in one luminaire. Fire rated for both standard timber joist and i-joist ceiling construction, Stellar includes 3CCT selectable colour which can be changed without removing the fitting from the ceiling.



Features

- 3CCT colour selectable - 3000K, 4000K & 6000K, operated from below the ceiling
- Fire rated to EN1365-2:2014 / BS476-21:1987 for standard timber and i-joist construction
- Acoustic rating designed to meet ISO10140 - 2 : 2010
- May be safely covered with thermal insulation
- Optional interchangeable bezels
- Tool-free plug & socket connection

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
SR/W	Stellar Fire Rated Downlight 6W 3CCT	600 lm		6W	100 lm/W

Product Information

Guarantee	5 Years
Colour Appearance (CCT)	3000K / 4000K / 6000K
IP Rating	IP65 (from below ceiling)
Voltage	230V
Material (Body/Housing)	Steel
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 80
Colour Finish	White RAL9003

LED Life Expectancy	L70B50 50,000 Hours
Power Factor	>0.85
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class II
Working Temperature	-20°C to 40°C

STELLAR

3CCT FIRE RATED DOWNLIGHT

Packaging Information

Dimensions (mm)	Ø: 86 x D: 31 mm
Product Net Weight (kg)	0.203 kg
Barcode	5055807623728
Box Dimensions (mm)	L:90 x W: 90 x D: 81 mm
Box Gross Weight (kg)	0.25 kg

Units/Outer Carton	48
Outer Carton Barcode	15055807623725
Outer Carton Dimensions (mm)	L: 385 x W: 385 x D: 355 mm
Outer Carton Gross Weight (kg)	12.28 kg

