

SPECIFICATION SHEET

110V LED NON-CORROSIVE FITTINGS



The LED 110V Non-Corrosive Fitting is complete with a one metre pre-wired flex and junction box for rapid deployment in site lighting applications.

Applications

- Site Lighting



Image shown SNCFP220C


Specification

LED:	48pcs of 0.2W SMD 2835
Material:	ABS and polycarbonate
Lumen Output:	1800lm
Colour Temperature:	4000K
Guarantee:	2 Years
Life Expectancy:	30,000 Hours
Working Temperature:	-10°C - 40°C (0°C - 40°C for emergency)
Power Factor:	0.5
Beam Angle:	120°
CRI:	80 Ra

Additional Information

- 3 / 4 Core 1m cable included.
- 4 Way terminal block included (can fit 2 x 1.5mm cables)
- 90lm/W
- Accessory pack included.
- Fast fit connector included.
- Hanging bracket included.
- Junction box included.
- Ni-Cd battery included in the emergency version.
- Opal diffuser
- 20mm gland sizes
- Painted metal LED tray included.
- Plastic clips included.
- Yellow finish

Dimensions



Code	Wattage	Emergency	Dimensions (L x W x D mm)
SNCFP220C	20W	No	665 x 105 x 110
SNCFP220EC	20W	Yes	665 x 105 x 110