

LOW TACK PVC TAPE



Product Code	Pricing Unit	Colour	Size	Pack Quantity	Pallet Quantity
TLT1	Each	Black	50mm x 33m	24	480
TLT01	Each	Orange	50mm x 33m	24	480
TLT2	Each	Black	75mm x 33m	16	320
TLT4	Each	Black	100mm x 33m	12	240

Product Description:

Our low-tack PVC tapes are ideal for joining protection materials such as the Proguard Protection Board. It is especially good for joining protection materials to sensitive surfaces as the low tack adhesive won't leave residue. Surfaces must be clean and free from dust for this product to work effectively.

Benefits:

- Removes without leaving residue.
- Water resistant.

Limitations:

- For extra sensitive surfaces use *Proguard Ultra Low Tack Tape*.
- Not 100% waterproof – if submerged under water this tape may come loose.

Application:

Temperature: between 0°C and + 35°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23 °C. Apply the tape by hand or with a *Proguard Tape Applicator*.

Performance Data:

Adhesive	Natural Rubber
Carrier	PVC film
Total Thickness	0.13±0.05mm
Adhesion to Steel	≥3n/in
Tensile Strength	≥35N/in
Rolling ball tack	≥10(Ball no.)
Elongation	≥150
Service temperature range	0°C -> + 80°C