

ELECTRIC LIFT PLATFORM—HIW2.0EU

An Electric Lift Platform can be used for many purposes including the raising and lowering of pallets. With a low profile of just 190mm, it can virtually eliminate the need for a pit. Ideal for production piece work, where repetitive bending and lifting operations can be eliminated, resulting in a happier work force. Can be floor or pit mounted

This electric lift platform is supplied with a remote power pack, fitted with a pedestal unit leading to the controls - up, down and a safety stop button. There is a further safety feature, which is the all round safety bar perimeter fitted to the table top, designed to halt descent when it comes into contact with any obstructions.



HIW2.0EU SPECIFICATIONS:

Capacity: 1000kg
Maximum Table Height: 1010mm
Minimum Table Height: 190mm
Platform Table Top Size: 1300x800mm
Lifting time: 25 seconds
Lifting speed with load: 40mm / second
Lowering speed with load: 35mm / second

Motor: 0.75KW
Net weight: 220kg
European electronic controlling system
Conforms to EN1570 and BSEN60204-1
3 Phase AC380v/50hz mains
Safety cut-off bars on all sides
High Quality Powder Coating

MIDLAND PALLET TRUCKS LTD
Part of the Midland Bearings Group of Companies
Building 33 Second Avenue, Pensnett Trading Estate,
Kingswinford, West Midlands. DY6 7UG

Telephone 01384 841440 Fax 01384 841450

Email. sales@midlandpallettrucks.com Website: www.midlandpallettrucks.com