



## Applications

Glass retaining strips

## Features & Benefits


- Easy side loading that allows you to change brad length without adjusting tool, plus E-Z Clear jam clearance
- Reduces fatigue throughout comfort-grip handle and the best balance and lowest recoil in the industry
- Superior power (40% more than comparable tools) makes it suitable for use on hardwood, plastics, and particleboard
- Oil-free design means easier maintenance and no lubrication to stain fine woods
- Precision-firing keeps work surface free of damage
- Rugged composition enables magazine to withstand on-the-job stress
- Requires minimum maintenance, with only two movable O-rings for virtually trouble-free upkeep
- Repair is easy, using only two Allen wrenches and the do-it-yourself Senco Parts Kit
- Comes complete in its own heavy-duty plastic case
- Muffler ensures quieter operation

## Glazing brad nailer

### Technical specifications

Dimension (LxWxH)	275x50x225 mm
Net weight	1,17 kg
Firing mode	Restrictive
Air inlet	1/4" female NPT
Operating pressure	4,8 - 8,3 bar
Air consumption (at 60 shots per minute)	54 l/m
Operating temperature range	-18 - 49 °C
Sound pressure level (Lpa)	79 dB
Sound power level (Lwa)	88 dB
Vibration level	under declaraton limit m/s <sup>2</sup>
Magazine capacity	110 pieces
Gauge	18 ga.
Collation type 1	Glue collated
Collation type 2	Glue collated
Collation angle	0 °

### Fastener specification



### Description

SLP20XP GLN, glazing brad nailer 1,2mm (AX)

### Art. Nr.

WCE0485

### EAN code

8715274044927