

WEATHERGUARD PRO

WATTAGE & CCT SELECTABLE NON-CORROSIVE

Weatherguard Pro is the latest version of our IP65 corrosion resistant luminaire. Featuring Plug & Play Emergency & Microwave kits (Inc corridor function), 4 Wattage & 3CCT Selectable, it makes these luminaires one of the most flexible options on the market. For ease of installation, the Weatherguard Pro has a newly developed housing with 11 conduit entry points & 4 adjustable terminal block locations. The gear tray and diffuser are combined and split from the body meaning all wiring can be completed directly to the base.



Features

- Stainless steel clips included as standard
- Includes accessory pack with mounting brackets, hanging adaptors and fixings
- Unique plug-in replaceable LED strips
- 7 Year Warranty
- High efficacy LED's 145lm/W

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
WGPRO6-60W-CCT	Weatherguard Pro 1800mm 34/42/51/60W 3CCT 3/4/6K P&P	4930lm 6090lm 7395lm 8700lm		34W 42W 51W 60W	145 lm/W

Product Information

Warranty	7 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	3000K 4000K 6000K
IP Rating	IP65
IK Rating	IK08
Voltage	220-240V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate

Colour Finish	Grey
LED Life Expectancy	L70B50 50,000 Hours
Power Factor	0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-20°C to 45°C



WEATHERGUARD PRO

WATTAGE & CCT SELECTABLE NON-CORROSIVE

Packaging Information

Dimensions (mm)	L: 1780 x W:76 x D: 81 mm
Product Net Weight (kg)	1.9 kg
Barcode	5055807630122
Box Dimensions (mm)	L: 1785 x W: 82 x D: 86 mm
Box Gross Weight (kg)	2.3 kg

Units/Outer Carton	9
Outer Carton Barcode	15055807630129
Outer Carton Dimensions (mm)	L: 1800 x W: 261 x D: 278 mm
Outer Carton Gross Weight (kg)	21.5 kg

