

Date: 13 October 2010

Information Sheet No.: TDS00111

EVO-STIK STICKS LIKE SH*T SEALANT

A HIGH STRENGTH, SINGLE-PART, MS POLYMER SEALANT

Evo-Stik Sticks Like Sh*t Sealant is a high performance, single component, moisture curing, modified silane (MS) polymer based sealant. It will bond damp surfaces and may even be used underwater. It has very low odour, cures to form a hard elastic rubber, with almost no shrinkage. It is of low hazard and it does not contain any water or solvent. When fully cured the Evo-Stik Sticks Like Sh*t Sealant may be painted with most types of paints. Before using this product refer to the relevant Health & Safety Data Sheet.

Features

- Can be applied to wet surfaces; even underwater.
- Waterproof, immediately after application.
- Mould resistant.
- Paintable, when cured.

Uses

- Bonds to most surfaces including wood, concrete, brick, plaster, glass, ceramics, metals, rigid pvc, grp, insulation boards and foam polystyrene.
- Bonds panels, signs, wallboards, skirtings etc. of the above materials.
- Interior & exterior use.

Product Characteristics

Colour White & Clear

Composition Moisture curing MS polymer, fillers, thickeners, additives.

Specific Gravity 1.5, approx.

Product Code 112216 White 290ml x 12
112223 Clear 290ml x 12

Shelf life/storage 12 months when stored in the original unopened containers. Store under dry conditions between 5°C and 25°C.

Typical Performance Data (approx.)

Full cure 24 hours approx. - dependent on temperature and humidity.

Skinning time 15-30 mins dependent upon temperature & humidity

Tack Free time 2-4 hours dependent upon temperature and humidity

Shore A hardness 50-55.

Tensile strength 1.5-1.8 MPA. (at 100% extension)

Elongation at break 200-300%.

Movement Will accommodate up to $\pm 15\%$ of the mean joint width.

Shrinkage Less than 3%

Temperature resistance -20°C to +100°C

Water Excellent resistance.

Abrasion Good resistance.

Coatings The cured sealant may be over-painted with most types of paints. In some rare cases the surface may retain slight tack, which usually another coat of the paint will cure. It is always advisable to test a small area to ensure compatibility.

Coverage Approx. 11.5 metres per 290ml.

Directions for use

IMPORTANT

Before using Evo-Stik Sticks Like Sh*t Sealant, please refer to the relevant Health & Safety Data Sheet. Available at www.bostik.co.uk named as the code above.

Date: 13 October 2010

Information Sheet No.: TDS00111

Preparation

1. Any loose or weak layers on the surface must be removed.
2. Surfaces must be clean and preferably dry.
3. Surfaces that are damp must be checked for weak or loose matter on the surface that the damp might hide. Any pooled water must be removed before application.

Application

1. Cut the cartridge nozzle at an angle at the point required to provide a suitable diameter bead of sealant.
2. Cut off the dome at the top of the cartridge without damaging the thread and secure nozzle onto it.
3. Fit the cartridge into the sealant gun, and then using it with the correct technique, force the Evo-Stik Sticks Like Sh*t Sealant into the joint, ensuring that it makes full contact with the sides.
4. The sealant surface can be improved by tooling to a smooth finish using a tooling stick dipped in soapy water.
5. Do not use a wetted finger.

Cleaning

1. Uncured product may be removed using cloths lightly dampened with white spirit, after carefully scraping off the bulk.
2. Cured product requires mechanical removal.

Precautions in Use

Evo-Stik Sticks Like Sh*t Sealant will not bond polythene, polypropylene & Teflon. Evo-Stik Sticks Like Sh*t Sealant must not be used on surfaces contaminated with bitumen.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Evo-Stik Sticks Like Sh*t Sealant.

Date: 13 October 2010**Information Sheet No.: TDS00111**

Sales & Technical contacts at Bostik	Telephone	Facsimile	Email addresses
Sales	0844 371 1192	01785 241818	customer.service@bostik.com
Technical advice	0844 371 1197	01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) sheets	01785 272625	01785 212962	stafford.gatehouse@bostik.com

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.