



SAFETY DATA SHEET

EVO-STIK LIQUID NAILS SOLVENTED

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME EVO-STIK LIQUID NAILS SOLVENTED

PRODUCT NO. V5730P, V5740Px

SUPPLIER BOSTIK LIMITED
COMMON ROAD
STAFFORD
STAFFORDSHIRE
ST16 3EH
+44 1785 272625
+44 1785 272650 (24 HOUR)
sds.uk@bostik.com

2 HAZARDS IDENTIFICATION

Highly flammable. Vapours may cause drowsiness and dizziness. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours are heavier than air and can travel long distances to a source of ignition Pilot lights can ignite the vapour Vapours may cause drowsiness and dizziness

CLASSIFICATION (1999/45) F;R11. R52/53, R67.

ENVIRONMENT

The primary environmentally hazardous substance in this formulation has been tested to Annex V of Directive 67/548/EEC by the supplier and has been reclassified as R51/53. This Product has therefore been reclassified to take into account the new information.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
NAPHTHA (PETROLEUM), HYDRODESULFURIZED LIGHT, DEAROMATIZED; <0.1% BENZENE	295-434-2	92045-53-9	10-30%	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT, <0.1% BENZENE	265-151-9	64742-49-0	5-10%	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
PROPAN-2-OL	200-661-7	67-63-0	< 1%	F;R11 Xi;R36 R67

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately!

SKIN CONTACT

Remove affected person from source of contamination. Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Water spray, fog or mist. Foam. Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc.

EVO-STIK LIQUID NAILS SOLVENTED

SPECIAL FIRE FIGHTING PROCEDURES

Keep run-off water out of sewers and water sources. Dike for water control. Cool containers exposed to flames with water until well after the fire is out. Move container from fire area if it can be done without risk. Use water spray to reduce vapours. If risk of water pollution occurs, notify appropriate authorities.

UNUSUAL FIRE & EXPLOSION HAZARDS

May explode when heated or when exposed to flames or sparks. May travel considerable distance to source of ignition and flash back. Vapour explosion and poison hazard indoors, outdoors and in sewers.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Avoid skin and eye contact. Ensure adequate ventilation. Wear personal protective equipment. Wear self contained breathing apparatus.

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Runoff or release to sewer, waterway or ground is forbidden. Absorb in vermiculite, dry sand or earth and place into containers. Do not let washing down water contaminate ponds or waterways. Collect in containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Provide good ventilation. Avoid spilling, skin and eye contact. Avoid acids, moisture, and combustible materials.

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Isolate from other materials. Store in tightly closed original container in a dry, cool and well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level.

ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation. Explosion-proof general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves. Use protective gloves made of: Nitrile.

EYE PROTECTION

Use approved safety goggles or face shield.

OTHER PROTECTION

Provide eyewash station. Wear suitable protective clothing as protection against splashing or contamination.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke. Use appropriate skin cream to prevent drying of skin.

EVO-STIK LIQUID NAILS SOLVENTED

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Paste
COLOUR	Yellowish
ODOUR	of solvents
FLASH POINT (°C)	-25

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

11 TOXICOLOGICAL INFORMATION

INHALATION

May cause irritation to the respiratory system.

INGESTION

Pneumonia may be the result if vomited material containing solvents reaches the lungs.

SKIN CONTACT

Liquid may irritate skin.

EYE CONTACT

Irritation, burning, lachrymation, blurred vision after liquid splash.

MEDICAL CONSIDERATIONS

Chronic respiratory and obstructive airway diseases. Skin disorders and allergies. History of smoking.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product contains a substance which may cause long term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	3		
PROPER SHIPPING NAME	ADHESIVES		
UN NO. ROAD	1133	UK ROAD PACK GR.	II
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	TUNNEL RESTRICTION CODE	(D/E)
HAZARD No. (ADR)	33	ADR LABEL NO.	3
HAZCHEM CODE	3YE	CEPIC TEC(R) NO.	30GF1-I+II, 30GF1-sp
RID CLASS NO.	3	RID PACK GROUP	II
UN NO. SEA	1133	IMDG CLASS	3
IMDG PACK GR.	II	EMS	F-E, S-D
UN NO. AIR	1133	AIR CLASS	3

EVO-STIK LIQUID NAILS SOLVENTED

AIR PACK GR.

II

15 REGULATORY INFORMATION

LABELLING



Highly Flammable

RISK PHRASES

R11	Highly flammable.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S2	Keep out of the reach of children.
S7	Keep container tightly closed.
S16	Keep away from sources of ignition - No smoking.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.

STATUTORY INSTRUMENTS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

GENERAL INFORMATION

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

INFORMATION SOURCES

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision. This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

ISSUED BY

Approved LJ

REVISION DATE July 2009

REV. NO./REPL. SDS GENERATED 7

DATE August 2006

RISK PHRASES IN FULL

R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable.
R36	Irritating to eyes.
R38	Irritating to skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.