

# Ceramix

## Ceramic Non-Slip Wall Tile Adhesive

Conforms to BS5980 as a Type 2, Class B adhesive and EN12004 Type D1T

- Ready mixed
- Easy to use
- Strong adhesion
- For use in bathrooms, showers and kitchens

Colour	Product Code	Pack Size	Box Qty
Off White/Buf	FBCERA3	3.5KG	4
	FBCERA7	7.5KG	1
	FBCERA15	15KG	1



## Tile Adhesives & Grouts

### Product Description

FEB CERAMIX CERAMIC NON SLIP WALL TILE ADHESIVE is an acrylic based formula for extra slip resistance and grab that is designed for general-purpose use in bathroom and kitchen areas. May be used in domestic showers when used in conjunction with FEB UNIFIL INTERIOR & EXTERIOR GROUT. Conforms to BS5980 as a Type 2, Class B adhesive and EN12004 Type D1T. FEB tile adhesives are formulated using only top quality raw materials and are designed to provide the correct product for fixing ceramic wall tiles and mosaics in most common applications.

### Typical Uses

- Fixing of ceramic wall tiles in bathrooms, kitchens and toilets. Must not be used externally.
- Suitable substrates: plaster, cement renderings, bricks, soundly painted surfaces, plywood, blockboard.
- Note: FEB CERAMIX is **not** suitable for use in areas subject to standing water. For fixing wall tiles internally in areas subject to prolonged wet conditions or condensation, use FEB WETMIX.
- Externally and for swimming pools and surrounds, use FEB PERMASET.
- When fixing ceramic tiles to floors, use FEB PERMASET or FEB FASTSET/FASTSET PLUS.

### Features & Benefits

- Non-slip/enhanced grip.
- Ready mixed.
- Easy to use.
- Strong adhesion.
- Suitable for domestic showers.
- Multi purpose.

### Instructions for Use

Surfaces to be tiled must be clean, dry and sound. Porous surfaces, including plaster, must be primed with FEBOND PVA diluted 1 to 4 with water and allowed to dry before tiling. Allow new plaster to dry at least one month before tiling. Apply adhesive to wall at a depth of 3-6mm (no less than 3mm, no greater than 6mm) combing out an area no greater than 1m<sup>2</sup> at a time. In dry situations, use a suitable notched trowel across the surface of the adhesive before placing the tiles into position and securing with a slight twist action to remove air voids.

In areas subject to wet conditions, do not use a notched trowel. Bed the tiles directly into the surface of the adhesive and again, secure with a slight twist action. In both situations, it is good practice to periodically remove a tile and check that at least 75% of the tile is covered in adhesive.

If this is not the case, apply fresh adhesive and reposition. All surplus adhesive must be removed whilst adhesive is still wet using a dampened cloth or sponge, particularly along grout lines.

### Coverage

Approximately 1.5kg/m<sup>2</sup> (6mm notched trowel) to 2.3kg/m<sup>2</sup> (solid bed).

### Storage

Store in cool dry conditions – PROTECT FROM FROST.

### Shelf Life

12 months from manufacture when stored in a sealed container and as recommended.

### Performance Data

Appearance	Off white/buff paste
Application Temp	+5°C to 35°C
Open time	15-25 mins. Do not apply more adhesive than can be tiled in 20 minutes.
Setting time	Allow to dry for 24 hours before grouting (72 hours if tiling on non-porous surfaces). Avoid wetting tiles for 48 hours. Showers should not be used for at least 7 days after grouting has been completed.

Ceramix