



Wetmix

Waterproof Ceramic Wall Tile Adhesive

Conforms to BS5980 as a Type 2, Class AA adhesive and EN12004 Type D2T

- Ready mixed
- Non-slip
- Easy to use
- Strong adhesion
- Ideal for heavy duty applications in wet areas
- For use in bathrooms, showers and kitchens

Colour	Product Code	Pack Size	Box Qty
Off White/Buf	FBWETMIX3	3.5KG	4
	FBWETMIX7	7.5KG	1
	FBWETMIX15	15KG	1



Tile Adhesives & Grouts

Wetmix

Product Description

FEB WETMIX WATERPROOF CERMAMIC WALL TILE ADHESIVE is a premium grade tile adhesive that can be used in areas subject to prolonged/ permanent wet conditions and in areas of high humidity and condensation. Conforms to BS5980 as a Type 2, Class AA adhesive and EN12004 Type D2T.

FEB tile adhesives are formulated using only top quality raw materials and are designed to provide the correct product for fixing ceramic wall tiles and mosaics in most common applications.

Typical Uses

Fixing ceramic wall tiles to showers, toilet areas, bathrooms and areas exposed to condensation - i.e. to any area subject to wet conditions (but excluding pools and external use). Can also be used for general fixing of ceramic wall tiles and expanded polystyrene tiles. Suitable substrates are plaster, cement render, glazed tiles or bricks, sound painted surfaces, plywood and blockboard or asbestos sheet.

NOTE: Externally and for swimming pools and surrounds, use FEB PERMASET. When fixing ceramic tiles to floors, use FEB PERMASET or FEB FASTSET/FASTSET PLUS.

Features and Benefits

- Non-slip.
- Ready mixed.
- Economical and easy to use.
- Rapid gain of water resistance.
- Suitable for showers and areas exposed to water or condensation.
- Good initial grab and strong adhesion.
- Low odour.

Instructions for Use

Surfaces to be tiled must be clean, dry and sound. Porous surfaces, including plaster, must be primed with FEBOND PVA diluted 1 to 4 with water and allowed to dry before tiling. Allow new plaster to dry at least one month before tiling. Apply adhesive to wall at a depth of 3-6mm (no less than 3mm, no greater than 6mm) combing out an area no greater than 1m² at a time. In dry situations, use a suitable notched trowel across the surface of the adhesive before placing the tiles into position and securing with a slight twist action to remove air voids.

In areas subject to wet conditions, do not use a notched trowel. Bed the tiles directly into the surface of the adhesive and again, secure with a slight twist action. In both situations, it is good practice to periodically remove a tile and check that at least 75% of the tile is covered in adhesive.

If this is not the case, apply fresh adhesive and reposition. All surplus adhesive must be removed whilst adhesive is still wet using a dampened cloth or sponge, particularly along grout lines.

Coverage

Approximately 1.5kg/m² (6mm notched trowel) to 2.3kg/m² (solid bed).

Storage

Store in cool dry conditions – PROTECT FROM FROST.

Shelf Life

12 months from manufacture when stored in a sealed container and as recommended.

Performance Data

Appearance	Off white/buff paste
Application Temp	+5°C to 35°C
Specification	15-25 mins. Do not apply more adhesive than can be tiled in 20 minutes.
Setting time	Allow to dry for 24 hours before grouting (72 hours if tiling on non-porous surfaces). Avoid wetting tiles for 48 hours. Showers should not be used for at least 7 days after grouting has been completed.

