

Black Bitumen Paint

Brush Applied Protective Coating For Metal, Concrete and Brickwork

- Protects gutters, downpipes & drains
- Long lasting & economical
- Coverage, 5-10m² per litre, depending upon texture & porosity

Colour	Product Code	Pack Size	Box Qty
Black	FBAQBTPNT1	1LTR	12
	FBAQBTPNT2	2.5LTR	6
	FBAQBTPNT5	5LTR	4
	FBAQBTPNT25	25LTR	1



Aquaseal Waterproofing Products

Product Description

FEB AQUASEAL BLACK BITUMEN PAINT is a general purpose black bitumen paint suitable for brush application.

Typical Uses

FEB AQUASEAL BLACK BITUMEN PAINT can be applied to most substrates, including iron and steel structures, metal fabrications, castings, asbestos cement sheeting, and structural concrete. NOTE FEB AQUASEAL BLACK BITUMEN PAINT is **NOT** suitable for use in fish ponds.

Features & Benefits

- Simple brush application.
- Rapid drying.

Instructions for Use

Preparation of Substrate

New surfaces must be cleaned to remove all traces of grease, oil and other foreign matter. All mill scale and any rust that has formed must be removed prior to painting. Where previous paint is firmly adhering and sound, it need not be removed. All loose flaking paint, scale, rust, dirt, grease etc., should be removed so that the surface is completely free from loose matter. On surfaces where all existing rust cannot be removed and where long term protection is required, use a fast drying red lead primer, zinc phosphate or other rust inhibitive primer in accordance with the manufacturer's instructions, and ensure this is dry before proceeding with the treatment. On clean, rust free surfaces where priming is required, apply one coat of FEB AQUASEAL FLASHING AND ROOF PRIMER by brush and allow to dry, under normal ambient conditions, for 20 - 40 minutes. Porous/ friable surfaces should also be primed with FEB AQUASEAL FLASHING AND ROOF PRIMER or a coat of FEB AQUASEAL BLACK BITUMEN PAINT diluted with 20% white spirits. FEB AQUASEAL BLACK BITUMEN PAINT can also be sprayed or dipped; for dipping it can be thinned if necessary using white spirit.

Application

A minimum of two coats is recommended to eliminate pinholes and inadequate coverage of high spots. Apply second coat after the first has dried.

Coverage

The generally recommended coverage rate for FEB AQUASEAL BLACK BITUMEN PAINT is:

Mild Steel 10m²/ltr per coat

Concrete (dependent on porosity) 5m²/ltr per coat

Tools and spillage may be cleaned using white spirit or paraffin

Storage

FEB AQUASEAL BLACK BITUMEN PAINT contains a flammable solvent and all precautions against fire must be taken during both storage and use.

Store in cool conditions. Keep away from sources of ignition. **No Smoking.** Refer to Health and Safety data sheet.

Shelf Life

Minimum two years when stored in unopened containers according to the manufacturer's instructions.

Performance Data

Specific Gravity at 15°C	0.9
Viscosity	1500 CP
Recommended covering capacity (on steel)	10m ² /ltr
Approx. Solids content W/W	56% ± 1%
Drying time at 15°C	2 - 4 hours
Flash Point (able closed cup) minimum	40°C
Film thickness per coat applied at 11m ² /ltr	Wet 0.1mm / Dry 0.05mm

Black Bitumen Paint