



HUSQVARNA A 25

SMART, PORTABLE AIR CLEANER

The A 25 is part of our latest generation of air cleaners, developed with a whole new level of intelligence and mobility to meet customer demands. Recommended for spaces up to 25 m² in a single-use set up.

A colour-coded visual alarm clearly indicates the filter status. The innovative units are compact and stackable – an advantage when it comes to maintenance, transportation and handling. The A 25 can be used as both an air cleaner and a negative air machine. Two- or three-stage filtering captures various particles commonly produced on a construction site, including silica dust and wood dust, as well as dust from metal, gypsum and other materials. The active carbon filter is available as an option.

FEATURES




MULTI-LEVEL MONITORING OF FILTER SATURATION

The LED light bar on the front of the machine provides a real-time visual indication of the filters' saturation level, represented by two colour bars. This helps you to ensure optimal air cleaning and plan filter maintenance.



WATER-PROTECTED FOR EASY DECONTAMINATION

The air cleaner has an IP54 classification, which means you can decontaminate it easily by hosing it down with water. Filters must be removed before washing the air cleaner with water.



EASY TO TRANSPORT

Handles on all sides make the air cleaner easy to carry. The unit is also stackable to save space.



EASY TO MAINTAIN

The smart and robust design allows easy access for service and maintenance, as well as making decontamination and filter changes easier.

FEATURES

SMART STORAGE

Integrated storage pocket on the back for smaller items such as cords.

THOROUGHLY TESTED ESSENTIAL FILTERS

To verify that particles are always filtered correctly, all essential filters are tested individually at each air-

cleaner model's maximum airflow. Each filter complies with the filtration level at maximum airflow stated on the filter: M/H-class, HEPA, H13, H14.

TECHNICAL SPECIFICATIONS

All specifications A 25	Art.no: 970 65 23-01 (230 V)	Art.no: 970 65 23-03 (110 V)
Voltage	220-240 V	110-120 V
Max current	1.0 A	1.9 A
Phases	~1	~1
Max power	230 W	209 W
Max airflow HEPA*	600 m ³ /hr	600 m ³ /hr
Max airflow HEPA + Pre-filter*	540 m ³ /hr	500 m ³ /hr
Max airflow HEPA + Pre-filter + Carbon filter*	400 m ³ /hr	410 m ³ /hr
Pre-filter area	0.34 m ²	0.34 m ²
Total essential filter area	3.0 m ²	3.0 m ²
Length	410 mm	410 mm
Width	340 mm	340 mm
Height	430 mm	430 mm
Weight	13.5 kg	13.5 kg
IP class	IPX4	IPX4

* Actual airflow value can differ up to 5% due to manufacturing tolerances.

ACCESSORIES



PRE FILTER 15-PACK

Art.no: 547 67 67-01



H13 ESSENTIAL FILTER

Art.no: 546 54 97-01



H14 ESSENTIAL FILTER

Art.no: 547 67 63-01



FILTER CARBON FILTER 5-PACK

Art.no: 547 67 62-01



INLET ADAPTER – A 25

Art.no: 547 08 28-01



INLET ADAPTER RING

Art.no: 547 08 29-01



OUTLET BAR – A 25

Art.no: 547 53 05-01



www.husqvarnaconstruction.co.uk