



18v AUTO FEED LXT SCREWDRIVER

DFR550Z

Models DFR550 and DFR750 have been developed as the advanced models of Model BFR440, featuring higher durability. These models feature a more reliable casing attachment.

18v AUTO FEED LXT SCREWDRIVER



TECHNICAL SPECIFICATIONS

| | |
|---------------------------|------------------------|
| Battery Type | Lithium-ion |
| Battery Quantity (3.0 Ah) | 0 |
| Body only machine | ✓ |
| Voltage | 18 v |
| Drywall screw | 55 mm |
| Max dry wall screw | 4mm x 55mm |
| Screw Size Range | 25 to 55 mm |
| Noise sound pressure | 78 dB(A) |
| Noise K factor | 3 dB(A) |
| No Load Speed | 4000 rpm |
| Vibration K factor | 1.5 m/sec ² |
| Vibration no load | 2.5 m/sec ² |
| Net weight | 2.1 - 3.1 kg |

USER BENEFITS

- Lithium-ion batteries have greater life spans than their Ni-MH or Ni-Cad counterparts giving 430% greater run time.
- Lithium-ion's 40% weight saving means 18 volt power can be obtained by a battery that weighs the same as a 12 volt Ni-MH battery.
- Anti-tilt device to prevent screws from swaying.
- Dust proof construction.
- Foldable screw guide that keeps the screw strip tangle free.
- Silent clutch.

[Link to product - www.makita.com](http://www.makita.com)



RELATED PRODUCTS

(Recon

■ OTHER