



# 18V AUTO-FEED SCREWDRIVER DFR750RME

Models DFR750 have been developed as the advanced models of Model BFR440, featuring higher durability. These models feature more reliable casing attachment with the following benefits: Rigid aluminum casing. Stopper base with anti-tilt device for preventing screws from swaying. Rubber cap securely fixed to stopper base. Dust-proof construction for smooth sliding action.



18V AUTO-FEED SCREWDRIVER

## TECHNICAL SPECIFICATIONS

Battery Type	Lithium-ion
Voltage	18 v
Battery quantity (4.0Ah)	2
Drywall screw	75 mm
Max dry wall screw size	4 - 75 mm
Screw Size Range	45 to 75 mm
Noise sound pressure	76 dB(A)
Noise K factor	3 dB(A)
No Load Speed	4000 rpm
Vibration K factor	1.5 m/sec <sup>2</sup>
Vibration no load	2.5 m/sec <sup>2</sup>
Net weight	2.1 - 3.2 kg

## USER BENEFITS

- Lithium-ion batteries have greater life spans than their Ni-MH or Ni-Cad counterparts giving 430% greater run time.
- Lithium-ion's 40% weight saving means 18 volt power can be obtained by a battery that weighs the same as a 12 volt Ni-MH battery.
- Anti-tilt device to prevent screws from swaying.
- Dust proof construction.
- Foldable screw guide that keeps the screw strip tangle free.
- Silent clutch.

Link to product - [www.makita.co.uk](http://www.makita.co.uk)



# RELATED PRODUCTS

(Recon

## STANDARD ACCESSORIES

DC18RC  
DC18RC COMPACT CHARGER



## OTHER