

18V Combi Drill LXT

DHP458RF3J

• Extremely compact tool size with an overall length of 225mm (8-7/8") • High power and productivity achieved with new DC motor (FD31-30) • Enhanced dust and drip-proof performance to ensure reliable operation even under bad weather.

18V Combi Drill LXT



TECHNICAL SPECIFICATIONS

| | |
|---------------------------|------------------------|
| Voltage | 18 v |
| Max. in wood | 65 mm |
| Max. in masonry | 16 mm |
| Max. in steel | 13 mm |
| Max Torque S/H | 58 / 91 Nm |
| Torque Settings | 21 + drill |
| Battery Type | Lithium-ion |
| Battery Quantity (3.0 Ah) | 3 |
| Vibration: Drilling | 9.5 m/sec ² |
| Vibration K factor | 1.5 m/sec ² |
| Net weight | 2.2 - 2.6 kg |
| Electric Brake | ✓ |
| Variable Speed Control | Trigger |
| Blows per Minute | 0-30000/6000 bpm |
| No Load Speed | 0-2000/400 rpm |

USER BENEFITS

- Enhanced dust and drip-proof performance for use in outdoor applications or harsh environments.
- Single sleeve keyless chuck allows for easy bit installation/removal by one hand.
- Twin LED Job light with pre-glow and afterglow functions
- Battery fuel gauge The power remaining in the battery can be indicated in 3 stages simply by pushing a button; 3 lights on: more than 50% of full battery capacity. 2 lights on: 20% to 50% of full battery capacity. 1 light on: less than 20% of full battery capacity

[Link to product - www.makita.com](http://www.makita.com)



RELATED PRODUCTS

(Reco

STANDARD ACCESSORIES

821550-0

MAKPAC CONNECTOR CASE (TYPE



837916-4

MAKPAC INLAY FOT TYPE 2 CASE



DC18RC

DC18RC COMPACT CHARGER



OTHER