

18Vx2 ROTARY HAMMER BL LXT DHR280ZWJ

28mm SDS-PLUS Cordless Combination Hammer powered by two 18V Li-ion batteries.

Includes DX08 Dust Collection system



TECHNICAL SPECIFICATIONS

Battery Type Lithium-ion Body only machine \checkmark Voltage 36 (18V x2) v Max in concrete 28 mm Max. in steel 13 mm Max. in wood 32 mm Max in concrete (TCT core) 54 mm Max in concrete (Diamond core) 65 mm Impact energy 2.8 J Shank SDS-PLUS Blows per minute 0 - 5,000 bpm Noise sound pressure 93 dB(A) Noise sound power 104 dB(A) Noise K factor 3 dB(A) No Load Speed 0 - 980 rpm Vibration K factor 1.5 m/sec² Vibration: Hammer Drilling 9.0 m/sec² Vibration: Chiselling 8.5 m/sec²

USER BENEFITS

- Includes DX08 Dust Collection System
- Brushless motor
- Electric brake
- · Variable speed control by trigger
- Constant speed control
- Forward / reverse rotation
- LED job light
- 3x Operating modes (RO/RH/HO)
- Torque limiter
- "Soft no load" function automatically reduces the motor speed during idling to suppress the vibration of the machine body.
- Anti vibration technology
- Powered by two 18V Li-ion batteries in series to supply energy to the powerful 36V DC motor drive system.



Link to product - www.makitauk.com

RELATED PRODUCTS

(Reco

STANDARD ACCESSORIES

199581-0

DX08 DUST EXTRACTION SYSTEM



821552-6

MAKPAC CONNECTOR CASE (TYPE



OPTIONAL ACCESSORIES

199581-0

DX08 DUST EXTRACTION SYSTEM



OTHER