



18V Impact Driver BL LXT

DTD153RTJ

Model DTD153 is a Cordless Impact Driver powered by 18V Li-ion battery and developed based model DTD129.



TECHNICAL SPECIFICATIONS

| | |
|---------------------------|-------------------------|
| Voltage | 18 v |
| Standard Bolt | M5-M16 |
| High Tensile Bolt | M5-M14 |
| Coarse thread (length) | 22 - 125 mm |
| Max Fastening Torque | 170 Nm |
| No Load Speed | 0 - 3400 rpm |
| Battery Type | Lithium-ion |
| Vibration: Fastening Bolt | 13.0 m/sec ² |
| Vibration K factor | 1.5 m/sec ² |
| Noise sound pressure | 96 dB(A) |
| Noise sound power | 107 dB(A) |
| Noise K factor | 3 dB(A) |
| Net weight | 1.3 - 1.6 kg |
| Battery Quantity (5.0ah) | 2 |
| Driving Shank | 6.35mm (1/4") Hex |
| Machine Screw | M4-M8 |
| Impacts per Minute | 0 - 3,600 ipm |

USER BENEFITS

- Brushless motor
- LED job light
- Ergonomic soft grip
- Electric brake
- Variable speed control by trigger
- Forward / reverse rotation
- Compact overall length.

[Link to product - www.makita.com](http://www.makita.com)



RELATED PRODUCTS

(Recom

STANDARD ACCESSORIES

197282-4

Battery BL1850B 18v Li-ion



821550-0

MAKPAC CONNECTOR CASE (TYPE



837670-0

INNER TRAY



DC18RC

DC18RC COMPACT CHARGER



OTHER