

18V Impact Driver BL LXT

DTD154Z

Model DTD154 is a Cordless Impact Driver powered by 18V Li-ion battery and developed based on DTD148.

18V Impact Driver BL LXT



TECHNICAL SPECIFICATIONS

Voltage	18 v
Standard Bolt	M5-M16
High Tensile Bolt	M5-M14
Coarse thread (length)	22 - 125 mm
Max Fastening Torque	175 Nm
Battery Type	Lithium-ion
Vibration: Fastening Bolt	12.5 m/sec ²
Vibration K factor	1.5 m/sec ²
Noise sound pressure	96 dB(A)
Noise sound power	107 dB(A)
Noise K factor	3 dB(A)
Body only machine	✓
Net weight	1.2 - 1.5 kg
Battery Quantity (5.0ah)	0
Impact Selection	3 stage + Tek mode
Driving Shank	6.35mm (1/4") Hex
Blows per Minute (Hi) - ipm	0 - 3800 ipm
Blows per Minute (Med) - ipm	0 - 2600 ipm

USER BENEFITS

- T-mode: Tightening mode for self-drilling screw
- Electronic 3-stage impact power selection (Hard/Medium/Soft)
- Brushless motor
- LED job light
- Ergonomic soft grip
- Electric brake
- Variable speed control by trigger
- Forward / reverse rotation
- Compact overall length.

[Link to product - www.makita.com](http://www.makita.com)



RELATED PRODUCTS

(Recom

■ OTHER