

18V Impact Driver BL LXT

DTD155Z

Model DTD155 is a cordless Impact Driver powered by 18V Li-ion battery and has been developed as an 18V version of TD111D.



TECHNICAL SPECIFICATIONS

Voltage	18 v
Standard Bolt	M5-M14
High Tensile Bolt	M5-M12
Coarse thread (length)	22 - 90 mm
Max Fastening Torque	140 Nm
Battery Type	Lithium-ion
Vibration: Fastening Bolt	14.0 m/sec ²
Vibration K factor	1.5 m/sec ²
Noise sound pressure	94 dB(A)
Noise sound power	105 dB(A)
Noise K factor	3 dB(A)
Body only machine	✓
Net weight	1.2 - 1.5 kg
Impact Selection	2 Stage + Assist mode
Driving Shank	6.35mm (1/4") Hex
Blows per Minute (Hi) - ipm	0 - 3900 ipm
Blows per Minute (Lo) - ipm	0 - 1600 ipm

USER BENEFITS

- New impact mode (A-mode): helps to eliminate "screw cam-out" and "cross threading" by driving at low speed until the start of tightening
- Brushless motor
- Electronic 2-speed Impact Power Selection
- Electric brake
- Variable speed control by trigger
- Forward / reverse rotation
- LED job light
- Ergonomically designed high comfort grip.
- Slim motor housing

[Link to product - www.makita.com](http://www.makita.com)



RELATED PRODUCTS

(Recon

■ OTHER