

52.5cc Blower 4ST

EB5300TH

EB5300TH is a petrol backpack blower equipped with a new 52.5mL 4-stroke engine in compliance with strict exhaust emission regulations.



TECHNICAL SPECIFICATIONS

Cubic Capacity	52.5 cc
Max air velocity	82 m/sec
Max air volume	15 m ³ /min
Noise sound pressure	96.0 dB(A)
Noise sound power	102.5 dB(A)
Noise K factor	1.6 dB(A)
Engine	4-stroke
Fuel Tank Capacity	1.8 litres
Fuel Type	Unleaded
No Load Speed	2800 - 6400 rpm
Vibration K factor	0.6 m/sec ²
Vibration no load	2.9 m/sec ²
Vibration Dampening	✓
Net weight	9.8 - 10.1 kg

USER BENEFITS

- Diaphragm carburetor
- Mechanical decompression valve
- Primer Pump
- Tube mounted throttle
- Comfortable backpack harness
- 4 damper springs mounted between the engine and the backpack frame that reduce vibration on the back of operator even during long hours.
- Telescopic pipe and nozzle
- Anti-Icing: You can open the anti-icing valve by simply turning a dial to supply warm air from the engine to prevent the carburettor from icing up under cold environments.
- Anti-static – Users hand is protected from static electric shock by enough insulation distance between grip and nozzle.
- Carry handle for easy transport
- In compliance with exhaust emission regulations: EPA Phase 2, EU Stage 2
- Powerful and environmentally friendly 4-stroke engine.

Link to product - www.makita.com



RELATED PRODUCTS

(Recom

■ OTHER