

COLLATED SCREWS

F-31153

Black phosphate collated screws for dry wall applications in steel and wood. Manufactured to DIN1812 certified to 48 hour salt spray test. High quality non jamming tapes.

COLLATED SCREWS



TECHNICAL SPECIFICATIONS

Screw Head	PH2
Model	BFR550/6843/6833 /6834/6835/ BFR440
Gauge	3.9
Coating	Phosphate
Thread type	Fine
Size	35
Screws per strip	50
Pack Quantity	20

USER BENEFITS

- Very fast and reliable auto-feed screwing. Minimal jamming
- Very fast and reliable auto-feed screwing. Minimal jamming
- Symmetrical head-geometry with centring-tip for optimised results in the event of reinforcement.
- Symmetrical head-geometry with centring-tip for optimised results in the event of reinforcement.
- Application: Autofeed, Drywall, dry-lining, plasterboard, steel and wood
- Application: Autofeed, Drywall, dry-lining, plasterboard, steel and wood
- Features: Black phosphate collated screws for dry wall applications in steel and wood. Manufactured to DIN1812 certified to 48 hour salt spray test.
- Features: Black phosphate collated screws for dry wall applications in steel and wood. Manufactured to DIN1812 certified to 48 hour salt spray test. Strip of 100 for use with Coil Feed screwdrivers
- Very fast and reliable auto-feed screwing
- Thread: Fine

EAN 0088381291712

[Link to product - www.makita.com](http://www.makita.com)

