

ANGLE GRINDER 125MM

GA5040C

1,400W angle grinder series models of GA4540C and GA5040C are successor models of 9560 series models, featuring:

•"Super Joint System II" developed for effective vibration absorption •Electronic current limiter, speed control and soft start •Anti-restart function



TECHNICAL SPECIFICATIONS

Bore Diameter	22.23 mm
Max Wheel Thickness	6 mm
Anti Restart Function	✓
Noise sound pressure	86 dB(A)
Noise sound power	97 dB(A)
Noise K factor	3 dB(A)
Max Wheel Diameter	125 mm
Input Wattage	1,400 w
No Load Speed	2800 - 11000 rpm
Vibration K factor	1.5 m/sec ²
Vibration: Sanding	2.5 m/sec ²
Vibration: Surface Grinding	6.5 m/sec ²
Net weight	2.5 - 3.6 kg

USER BENEFITS

- Anti-restart function.
- Constant speed control
- Soft start.
- Electronic current limiter for overload protection.
- Variable speed control dial.
- Super Joint System II" provides increased machine durability by absorbing the vibration produced by the wheel grinding or cutting material.
- Ergonomically best possible barrel grip, with a perfect circumference size and shape which fits the hand for extra comfortable handling.
- Tool-less wheel cover is adjustable to any desired position.
- Double Insulation
- Lock-on switch to reduce user fatigue.

[Link to product - www.makita.com](http://www.makita.com)



RELATED PRODUCTS

(Recom

■ OTHER