

# 40Vmax COMBI DRILL BL XGT

## HP001GD102

HP001G is cordless combi drill powered by 40Vmax XGT Li-Ion battery, and developed as the top-of-the-range model of our BL motor range of cordless combi drills.



### TECHNICAL SPECIFICATIONS

Capacity in Steel	20 mm
Capacity in Wood	76 mm
No Load Speed (Hi)	0 - 2,600 rpm
No Load Speed (Lo)	0 - 650 rpm
Blows per Minute (Hi) - ipm	0 - 39,000 ipm
Blows per Minute (Lo) - ipm	0 - 9,750 ipm
Capacity in Masonry	20 mm
Voltage	40 v
Torque Settings	21 (Hi) / 41 (Lo)
Battery Type	Lithium-ion
Vibration K factor	1.5 m/sec <sup>2</sup>
Noise sound pressure	85 dB(A)
Noise sound power	96 dB(A)
Noise K factor	3 dB(A)
Net weight	2.7 – 3.0 kg
Battery Quantity (2.5Ah)	1
Max. Fastening Torque (Soft Joint)	68 Nm
Max. Fastening Torque (Hard Joint)	140 Nm

### USER BENEFITS

- Brushless motor
- Forward / reverse rotation
- Single sleeve keyless chuck allows for easy bit installation/removal by one hand.
- Electric brake
- 2 mechanical gears.
- Variable speed control by trigger
- LED job light
- Active Feedback Sensing Technology (AFT): Shuts down the tool if the rotation speed suddenly slows down
- Electronic clutch
- Digital display for visual confirmation of selected torque
- Excellent performance in continuous heavy duty applications

Link to product - [www.makita.com](http://www.makita.com)



# RELATED PRODUCTS

(Recom

## ■ STANDARD ACCESSORIES

821551-8

MAKPAC CONNECTOR CASE (TYPE



## ■ OTHER