

# Combi Drill 10mm

## HP0300

HP0300 is a corded hammer driver drill developed for cost-conscious users



### TECHNICAL SPECIFICATIONS

Max. in steel	10 mm
Max. in masonry	8 mm
Max. in wood	28 mm
Input wattage	320 w
Vibration K factor	2.0 m/sec <sup>2</sup>
Noise sound pressure	82 dB(A)
Noise sound power	93 dB(A)
Noise K factor	3 dB(A)
Net weight	1.3 kg
Chuck Capacity	10 mm
Blows per Minute (Hi) - ipm	0 - 22,500 ipm
Blows per Minute (Lo) - ipm	0 - 6750 ipm
No Load Speed (Hi)	0 - 1500 rpm
No Load Speed (Lo)	0 - 450 rpm
Max Torque S/H	21 / 56 Nm
Torque Settings	20 + Drill
Vibration: Impact drilling into concrete	12.5 m/sec <sup>2</sup>
Vibration: Drilling into metal	2.5 m/sec <sup>2</sup>

### USER BENEFITS

- Forward / reverse rotation
- 2 mechanical gears.
- Variable speed control by trigger
- Double Insulation
- 2.5m power supply cord
- Keyless Chuck
- Lock-on function
- Ergonomically designed handle with soft grip.

[Link to product - www.makita.com](http://www.makita.com)



# RELATED PRODUCTS

(Recom

## ■ OTHER