

40Vmax ROTARY HAMMER BL XGT HR003GD101

HR003G is a cordless combination hammer powered by 40Vmax XGT Li-lon battery.



TECHNICAL SPECIFICATIONS

Battery Type Lithium-ion 40 v Voltage Battery Quantity (2.5Ah) Max in concrete 28 mm Max. in steel 13 mm Max. in wood 32 mm Max in concrete (TCT core) 54 mm Max in concrete (Diamond core) 65 mm Impact energy 2.8 J Shank SDS PLUS Blows per minute 0 - 5,000 bpm Noise sound pressure 93 dB(A) Noise sound power 104 dB(A) Noise K factor 3 dB(A) No Load Speed 0 - 980 rpm Vibration K factor 1.5 m/sec² Vibration: Hammer Drilling 7.0 m/sec² Vibration: Chiselling 7.0 m/sec²

USER BENEFITS

- Brushless motor
- Electric brake
- · Variable speed control by trigger
- Constant speed control
- Forward / reverse rotation
- LED job light
- 3x Operating modes (RO/RH/HO)
- Torque limiter
- "Soft no load" function automatically reduces the motor speed during idling to suppress the vibration of the machine body.
- Anti vibration technology



Link to product - www.makitauk.com

RELATED PRODUCTS

(Reco

STANDARD ACCESSORIES

821552-6 MAKPAC CONNECTOR CASE (TYPE



OTHER