

40Vmax ROTARY HAMMER BL XGT HR004GD202

HR004G is cordless combination hammer powered by 40Vmax XGT Li-Ion battery.



TECHNICAL SPECIFICATIONS

Battery Type	Lithium-ion
Voltage	40 v
Battery Quantity (2.5Ah)	2
Max in concrete	28 mm
Max. in steel	13 mm
Max. in wood	32 mm
Max in concrete (TCT core)	54 mm
Max in concrete (Diamond core)	65 mm
Impact energy	2.9 J
Shank	SDS PLUS
Blows per minute	0 - 5,000 bpm
Noise sound pressure	93 dB(A)
Noise sound power	104 dB(A)
Noise K factor	3 dB(A)
No Load Speed	0 - 980 rpm
Vibration K factor	1.5 m/sec ²
Vibration: Hammer Drilling	6.5 m/sec ²
Vibration: Chiselling	7.5 m/sec ²

USER BENEFITS

- Supplied with DX14 Dust Extraction System
- Brushless motor
- Electric brake
- Variable speed control by trigger
- Constant speed control
- Forward / reverse rotation
- LED job light
- 3x Operating modes (RO/RH/HO)
- Torque limiter
- "Soft no load" function automatically reduces the motor speed during idling to suppress the vibration of the machine body.
- Anti vibration technology
- Supplied with Quick Change Chuck

[Link to product - www.makita.com](http://www.makita.com)



RELATED PRODUCTS

(Recon

■ STANDARD ACCESSORIES

821552-6

MAKPAC CONNECTOR CASE (TYPE



■ OTHER