

Rotary Hammer SDS+ 26mm

HR2630T

Model HR2630 is a 26mm (1") combination hammer based on predecessor model HR2610 but with improved operation mode change lever.

HR2630T is fitted with a quick change drill chuck.
Rotary Hammer SDS+ 26mm



TECHNICAL SPECIFICATIONS

Impact energy	2.4 J
Max in concrete (TCT bit)	26 mm
Max in concrete (TCT core)	68 mm
Max in concrete (Diamond core)	80 mm
Max in wood	32 mm
Max in steel	13 mm
Impacts per minute	0 - 4,600 ipm
Input Wattage	800 w
Net weight	3.0 - 3.5 kg
No Load Speed	0 - 1200 rpm
Vibration: Chiselling	10.5 m/sec ²
Vibration: Hammer Drilling	15.5 m/sec ²
Noise sound pressure	91 dB(A)
Noise K factor	3 dB(A)
Noise sound power	102 dB(A)
Vibration: Drilling into metal	2.5 m/sec ²

USER BENEFITS

- Modified operation-mode change lever enables switch from 'Rotation' to 'Hammering' mode and vice-versa without rotating the chuck.
- 3 mode operation: Rotation only / Rotation with hammering / Hammering only
- Supplied with Quick Change Chuck
- Variable speed control by trigger
- Forward / reverse rotation
- Torque limiter
- Double Insulation
- 40 different bit angle settings
- Compact and lightweight design
- Depth stop
- Ergonomically designed handle with rubberised soft grip fits your hand perfectly to provide maximum control and comfort.

[Link to product - www.makita.com](http://www.makita.com)



RELATED PRODUCTS

(Recom

■ OPTIONAL ACCESSORIES

195180-6
DUST COLLECTING CUP



■ OTHER