

Rotary Hammer SDS+ 26mm

HR2650

HR2650 series are 2kg class Combination Hammer developed based on the current HR2630 series by adding a new dust collection system.



TECHNICAL SPECIFICATIONS

Impact energy	2.4 J
Max in concrete (TCT bit)	26 mm
Max in concrete (TCT core)	68 mm
Max in concrete (Diamond core)	80 mm
Max in wood	32 mm
Max in steel	13 mm
Impacts per minute	0 - 4600 ipm
Input Wattage	800 w
Vibration K factor	1.5 m/sec ²
Net weight	3.0 - 4.1 kg
No Load Speed	0 - 1200 rpm
Vibration: Chiselling	9.5 m/sec ²
Vibration: Hammer Drilling	12.5 m/sec ²
Noise sound pressure	91 dB(A)
Noise K factor	3 dB(A)
Noise sound power	102 dB(A)
Vibration: Drilling into metal	2.5 m/sec ²

USER BENEFITS

- Dust collecting port on telescopic guide with a sliding range of 190mm
- Secure connection between dust case and dust collecting section
- Equipped with HEPA filter
- Transparent dust case
- Easy disposal of dust and easy cleaning of dust case
- 3 mode operation: Rotation only / Rotation with hammering / Hammering only
- One touch sliding chuck for easy bit installation and removal.
- Variable speed control by trigger
- Forward / reverse rotation
- Torque limiter
- Double Insulation
- 40 different bit angle settings
- Compact and lightweight design
- Depth stop
- Ergonomically designed handle with rubberised soft

Link to product - www.makitauk.com



RELATED PRODUCTS

(Recon

■ OTHER