

# 260mm Slide Compound Mitre Saw LS1019L

260mm Slide Compound Mitre Saw. Motor head slides on fixed pipes without extending to the rear of the machine, allowing the machine to be placed close to the wall.

LS1019L features laser marker



## TECHNICAL SPECIFICATIONS

Blade Diameter	260 mm
Max mitre range	60 - 60 °
Max mitre cut at 90°	68 x 310 mm
Bore Diameter	30 mm
Max bevel range	48 - 48 °
Noise sound pressure	91 dB(A)
Noise sound power	101 dB(A)
Noise K factor	3 dB(A)
Input Wattage	1510 w
No Load Speed	3200 rpm
Vibration K factor	1.5 m/sec <sup>2</sup>
Vibration no load	2.5 m/sec <sup>2</sup>
Net weight	26.3 kg

## USER BENEFITS

- Built in laser guide.
- Motor head slides on fixed pipes without extending machine at rear end, so the machine can be placed close to wall.
- Front knob for easy bevel adjustment
- Holders to support a wide workpiece
- Easy-to-operate mitre angle lock
- One-touch sliding lock
- Large turn base
- Connects to dust extractor
- Electric brake
- Soft start
- Constant speed control
- Double Insulation

Link to product - [www.makita.com](http://www.makita.com)



# RELATED PRODUCTS

(Recom

## ■ OTHER