



40Vmax IMPACT DRIVER BL XGT TD001GD103

TD001G is a cordless impact driver powered by 40Vmax XGT Li-Ion battery



TECHNICAL SPECIFICATIONS

Voltage	40 v
Standard Bolt	M5-M16
High Tensile Bolt	M5 – M14
Coarse thread (length)	22 - 125 mm
Max Fastening Torque	220 Nm
Blows per Minute (Max) - ipm	0 - 4,400 ipm
Battery Type	Lithium-ion
Vibration K factor	1.5 m/sec ²
Noise sound pressure	96 dB(A)
Noise sound power	107 dB(A)
Noise K factor	3 dB(A)
No Load Speed (max/hard/med/soft)	0- 3700 / 3200 / 2100 / 1100 rpm
Vibration: Impact tightening of fasteners @ max capacity	10.0 m/sec ²
Battery Quantity (2.5Ah)	1
Driving Shank	6.35mm (1/4") Hex
Blows per Minute (Hi) - ipm	0 - 3,600 ipm
Blows per Minute (Med) - ipm	0 - 2,600 ipm

USER BENEFITS

- Electronic 4-stage impact power selection + 6x Assist Modes
- 6x Assist modes (2x T-modes, 1x Wood mode, 3x Bolt modes)
- Brushless motor
- Electric brake
- Variable speed control by trigger
- Constant speed control
- Quick mode switching function with memory function
- Forward / reverse rotation
- LED job light
- Ergonomically designed high comfort grip.
- One touch sliding chuck for easy bit installation and removal.

Link to product - www.makita.com



RELATED PRODUCTS

(Recom

■ STANDARD ACCESSORIES

821550-0

MAKPAC CONNECTOR CASE (TYPE



■ OTHER