



# 12Vmax Impact Driver CXT

## TD110DWAE

Model TD110D is one of the first new 12V max platform models. Featuring increased motor power for higher application speed and max tightening torque



### TECHNICAL SPECIFICATIONS

Voltage	12 v
Drive shank Hex	1/4 "
Standard Bolt	M5-M12
High Tensile Bolt	M5-M10
Coarse thread (length)	22 - 90 mm
Impacts	0 - 3,500 ipm
Max Torque	110 Nm
No Load Speed	0 - 2600 rpm
Battery Type	Lithium-ion
Vibration: Fastening Bolt	8.0 m/sec <sup>2</sup>
Vibration K factor	1.5 m/sec <sup>2</sup>
Noise sound pressure	94 dB(A)
Noise sound power	105 dB(A)
Noise K factor	3 dB(A)
Net weight	1.0 - 1.2 kg
Battery Quantity (2.0Ah)	2
Machine Screw	M4-M8

### USER BENEFITS

- Slide type Li-ion battery
- Electric brake
- Variable speed control trigger.
- Equipped with Battery protection circuit: designed to protect the battery from damages due to overdischarge, high temperature or overload current.
- Forward and reverse trigger.
- LED job light
- Ergonomic soft grip

Link to product - [www.makita.com](http://www.makita.com)



# RELATED PRODUCTS

(Recom

## STANDARD ACCESSORIES

**197396-9**

Battery BL1021B



**DC10WD**

12Vmax Standard Charger



## OTHER