

MULTI TOOL

TM3000CX4

Extra versatile oscillating Multi-Tool. Wide selection of accessories available for various applications.

MULTI TOOL



TECHNICAL SPECIFICATIONS

Oscillation Angle	3.2 °
Oscillations per Minute	6000 - 20000
Input Wattage	320 w
Vibration K factor	1.5 m/sec ²
Vibration: Cutting Metal	3 m/sec ²
Vibration: Cutting Wood	6.5 m/sec ²
Vibration: Chiselling	5.5 m/sec ²
Vibration: Sanding	2.5 m/sec ²
Net weight	1.4 - 1.5 kg

USER BENEFITS

- Thumb On/Off switch, positioned for ease of use when holding body of machine.
- Hex wrench holder on body.
- Variable speed control dial.
- Optional dust extraction attachment (Not included)
- Accessories can be installed at 30° increments, across 360°
- Uses OIS interface.

[Link to product - www.makita.com](http://www.makita.com)



RELATED PRODUCTS

(Recon

STANDARD ACCESSORIES

B-21624

DELTA RED 60G 10PC



B-21646

DELTA RED 120G 10PC



B-21652

DELTA RED 180G 10PC



B-21630

DELTA RED 80G 10PC



B-21668

DELTA RED 240G 10PC



B-22947

DELTA RED 100G 10PC



B-22953

DELTA RED 150G 10PC



OTHER