

# L Class Dust Extractor 20L

## VC2012L

Wet and dry L-class dust extractor.

Class L - Removes 99.0% of dust with limit value for occupational exposure >1.0mg/m<sup>3</sup>

Suitable for processes involving mica, china clay, gypsum.



### TECHNICAL SPECIFICATIONS

Power take off wattage (240V)	2000 W
Max Airflow	3.6 m <sup>3</sup> /min
Dust Bag Capacity	19 litres
Max Sealed Suction	21.0 kPa
Tank Capacity	20 litres
Tank capacity Wet	12 litres
Noise sound pressure	72 dB(A)
Hose length	3.5 m
Hose Diameter	32 mm
Input Wattage	1000 w
Net weight	8 kg

### USER BENEFITS

- Motor head design with flat top and tool deposit.
- Innovative hose storage solution with flexible rubber strap.
- Washable PET cartridge filter protects turbine by holding back fine dust and debris.
- Fleece filter bag allows you to pick up most debris without damaging the filter bag.
- Push and clean system: takes just seconds to clean the filter.
- Automatic On/Off function: machine activates when a connected power tool is used. 240V only
- Integrated carry handle makes lifting and tilting of container easy and convenient.
- Protection level IP24
- 240V model only includes power take off (2000W)
- Inox container

Link to product - [www.makitauk.com](http://www.makitauk.com)



# RELATED PRODUCTS

(Recon

## ■ OTHER