



EX60 & EX125

EX60



- Non-rechargeable safety approved LED flashlight
- ATEX rating: Zone 0 EX II 1G Ex ia IIC T4 iaD T135C
- UL: Class I DIV I GRAP ABC, Class II DIV GRP EFG, Class III, TEMP CODE: T4
- Osram golden dragon LED
- Aluminium heat sink enhancing LED efficiency
- Waterproof up to 3m (IP68)
- Robust durable casing and impact resistant lens
- Push button tail end switch
- Non-slip rubber grip handle
- Supplied with wrist strap



Optional helmet clips




EX60 & EX125

These LED flashlights are totally safe in hazardous areas. Rated at Atex zone 0 they are widely used by the emergency services and ideal for using in mining, petrochemical and gas industries.

EX60	
14h	0.101kg
Run time	14h
Battery	4 x AA
Product weight (kg)	0.101
Boxed weight (kg)	0.187
Product size (mm)	L170 x 40 ø
Boxed size (mm)	L210 x W90 x H60
Part No.	NSEX60

EX125



- Cree XP-E LED
- Two ways position clip
- 2 Modes: high and low
- Fastener prevents opening torch in hazardous places
- Valve design to hydrogen gas release

EX125	
60h 40h	0.190kg
Run time	60h 40h
Battery	3 x C Cell
Product weight (kg)	0.190
Boxed weight (kg)	0.349
Product size (mm)	L225 x 60 ø
Boxed size (mm)	L235 x D62 x H62
Part No.	NSEX125

CERTIFICATION & STANDARDS EX60 & EX125

UL	CLASS I DIV IGRP ABCD CLASS II DIV I GRP EFG CLASS III TEMP CODE: T4
ATEX	II 1 G Ex ia IIC T4
IECEX	Ex ia IIC T4 Ga
CE	Approved
ROHS	Approved
REACH	Approved