

protection

OIL HOSE REEL RETRACTABLE 10MTR

MODEL NO: AK4567D

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.









Wear protective gloves

Wear protective clothing

manual 1. SAFETY

- □ WARNING! Ensure health & safety, local authority, and general workshop practice regulations are strictly adhered to when using this equipment.
- ✓ Familiarise yourself with product application and limitations, as well as the specific potential hazards peculiar to this product.
- ✓ Maintain the hose reel in good condition (use an authorised service agent).
- Replace or repair damaged parts. Use genuine parts only. Non authorised parts will invalidate the warranty.
- ✓ Use only lubricants up to SAE 150 viscosity and antifreeze liquids.
- Ensure safety eye protection and protective clothing are worn when using this product.
- Remove ill fitting clothing. Remove ties watches rings, other loose jewellery and contain and/or tie back long hair.
- ✓ Keep the work area clean, uncluttered and ensure there is adequate lighting.
- ✓ Maintain correct balance and footing. Ensure the floor is not slippery and wear non slip shoes.
- ✓ Keep children and unauthorised persons away from the working area.
- ✓ After use, drain any fluids from the equipment before storage.
- Dispose of waste liquids in accordance with local authority regulations.
- ✓ Disconnect air pressure from equipment when not in use.
- **DO NOT** exceed the maximum working pressure of 2000psi.
- **DO NOT** leave the hose on the ground, retract when not in use.
- **DO NOT** point attachments at people or animals.
- **DO NOT** use the equipment near open flames.
- **DO NOT** smoke whilst using this equipment.
- **DO NOT** use with corrosive fluids.
- **DO NOT** dismantle, tamper with or adapt the reel for any purpose other than for which it is designed.
- DO NOT use the unit if it has been dropped or mishandled, check the unit to ensure there is no damage.
- ✓ Keep the equipment clean and store in a safe dry, childproof location.
- WARNING! DO NOT dismantle the hose reel casing. To do so may result in damage to the appliance and/or personal injury and will invalidate the warranty.
- WARNING! DO NOT allow uncontrolled discharge of fluids thus polluting the environment. All liquids must be disposed of according to local authority regulations.

2. INTRODUCTION

For use with AK4560D pump station. Heavy-duty steel and powder coating finish for corrosion resistance. Four roller fairlead allows smooth running of hose whatever the angle of hose or mounting position of reel. Multi position ratchet lock with fully enclosed spring. Includes 1.5mtr connection hose for connecting reel to pump.

3. SPECIFICATION

Model no:	AK4567D
Hose inlet/outlet:	1/2"BSP
Hose length:	10mtr
Hose size (ID):	1/2"
Max. pressure:	2000psi
Weight:	18.14ka

4. MOUNTING

- 4.1. Mount the reel to a wall or bench using appropriate fixings (not supplied).
- Connect the 1.5mtr hose from the centre reel connection to the AK4560D pump station.
- 4.3. Connect a dispensing gun/meter to the outlet connection.



5. OPERATION

- 5.1. Pull the hose at a steady pace, a clicking noise from the ratchet will be heard, when the hose is at the desired length, gently release the pressure and the hose will lock into position.
- 5.2. To retract the hose, pull the hose out a short distance and release the hose will now rewind.
 - □ WARNING! DO NOT let go of the hose, guide it back until it is fully retracted. Failure to do this may damage the gun or metering device on the end of the hose.

6. MAINTENANCE

- □ WARNING! Before attempting maintenance or inspection vent any pressure remaining in the hose and empty hose of oil etc.
- 6.1. To ensure reliable operation, inspect, clean hose and casing regularly. **DO NOT** spray or wet the product but clean with a damp cloth.
- **DO NOT** use solvents or detergents as these may cause permanent damage.
- 6.2. The hose reel does not require special maintenance as it is lubricated for life. If the product needs attention, consult your nearest authorised service agent.
 - WARNING! DO NOT attempt to loosen or remove any part of the product. Replacement of the supply hose should be carried out by skilled personnel only, contact your nearest authorised service agent.
- 6.3. Store in a cool, dry, childproof place.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR

1 01284 757500 01284 703534 🔯 sales@sealey.co.uk 🕏 www.sealey.co.uk