

DIGITAL TYRE TREAD DEPTH GAUGE MODEL NO: VS0560.V2

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions and maintained properly, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



A BATTERY WARNING KEEP OUT OF REACH OF CHILDREN In case of ingestion seek medical attention immediately.



instruction manual

1. SAFETY

- WARNING! Ensure Health and Safety, local authority and general workshop practice regulations are adhered to when using tools and equipment.
- DO NOT use gauge if damaged. X

Batteries in

product

- Maintain gauge in good and clean condition for best and safest performance.
- Keep children and unauthorised persons away from the work area. 1
- DO NOT use the gauge for any purpose other than for which it is designed. X
- DO NOT get gauge wet or use in damp or wet locations, or areas where there is condensation. Keep gauge clean and dry using a dry cotton X cloth only
- DO NOT expose gauge to bright sunlight or dust. X
- DO NOT dismantle gauge. X
- DO NOT apply any voltage to the gauge. X
- The gauge is a precision instrument, treat with care, avoid using force and do not subject to knocks or shocks. 1
- Take particular care not to damage or scratch the scale surface. ./
- Use gauge in a reasonably constant temperature conditions of approximately 20°C.
- When not in use, turn off and store gauge in a safe, dry, childproof location. 1

2. INTRODUCTION

Hardened and tempered stainless steel gauge. 11mm High figures in LCD display for ease of reading. Metric and Imperial calibration with conversion between the two. Zero setting control allows for comparative measurement. Supplied in storage case.

3. SPECIFICATION


Model No:
Range:
Resolution:0.01mm(0.0005")
Accuracy:±0.02mm(0.001")
Battery: SR44 - 1.5V (supplied)

OPERATION 4.

- Turn on gauge by pressing 'On-Off' switch. Wait at least one 31 second before use.
- Use the "mm/Inch" button to toggle between inches and mm at 3.2. anv time.
- Press the "Zero" button at any time to zero the reading. 3.3.

5. BATTERY FITTING

- **FITTING A NEW BATTERY** 5.1
- A flashing display indicates that the battery is exhausted replace as follows:
- 5.1.1. Remove battery cover by sliding backward and lifting the lower edge.
- 5.1.2. Remove exhausted battery and fit replacement with +ve side uppermost.
- 5.1.3. Dispose of old battery in a safe and approved manner. Do not burn.
 - If the display fails to alter when the slide is moved, remove the battery, wait at least 30 seconds and then refit the battery.







ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.





WEEE REGULATIONS

Dispose of this product at the end of its working life in compliance with the EU Directive on Waste Electrical and Electronic Equipment (WEEE). When the product is no longer required, it must be disposed of in an environmentally protective way. Contact your local solid waste authority for recycling information.



BATTERY REMOVAL See section 5. Under the Waste Batteries and Accumulators Regulations 2009, Jack Sealey Ltd are required to inform potential purchasers of products containing batteries (as defined within these regulations), that they are registered with Valpak's registered compliance scheme.

Jack Sealey Ltd Batteries Producer Registration Number (BPRN) is BPRN00705.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Please note that other versions of this product are available. If you require documentation for alternative versions, please email or call our technical team on technical@sealey.co.uk or 01284 757505.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR