

OIL FILTER DRAIN TUBE - OIL FILTER DRAIN TUBE & BOTTLE MODEL NO: VS7010 & VS7110

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



- ✓ Keep the drain tube and bottle clean and maintain it in good condition.
- Replace or repair damaged parts. Use genuine parts only. Unauthorised parts may be dangerous and will invalidate the warranty.
- \checkmark Keep all non-essential persons away from the work area.
- ✓ Check connections and fittings before use.
- Ensure that the bottle capacity exceeds the amount of fluid to be collected.
- **x DO NOT** use for any purpose other than that for which it is designed.
- DO NOT operate if any parts are damaged or missing as this may cause failure and/or personal injury.
- **x DO NOT** leave drain tube and bottle operating unattended.
- IMPORTANT! Ensure that you wear protective clothing, gloves, goggles, face mask as appropriate for the fluid being extracted.
- WARNING! DO NOT allow uncontrolled discharge of fluids thus polluting the environment.
- \checkmark Dispose of waste fluids in accordance with local authority regulations.
- WARNING! DO NOT use with gasoline or other flammable liquids.
- DO NOT use the unit to extract dangerous chemicals, poisons, acids, alkaline or solvents.
- \checkmark The container is not designed for long term storage.
- **× DO NOT** store the unit under extreme conditions.
- DO NOT adapt the unit for any other purpose.
- \checkmark When not in use, store in a safe, dry, childproof area.

2. INTRODUCTION

Model No. VS7010 Designed to attach to the oil filter housing on VAG FSi petrol engines. Allows the filter housing to be drained before removal, preventing spillage. Use in conjunction with a suitable oil drainer. Model No. VS7110 Features a control valve fitted to the bottle and hanging chain.


3. OPERATION

- 3.1. With the vehicle on a suitable ramp drain engine oil.
- 3.2. Locate the oil filter (black plastic housing).
- 3.3. Remove the dust cover on the bottom of the housing to expose the red bleed valve.
- 3.4. **VS7110** Secure drain bottle using the retaining chain and open valve, on top of the drain bottle.
- 3.5. Screw the adaptor into the end of the plastic housing. Screwing in the adaptor will release the red bleed valve in the filter housing which allows the oil to drain.
- 3.6. Once fully drained unscrew adaptor.
- 3.7. The filter housing can now be removed from the engine using the large hex located at the bottom of the filter housing.

4. MAINTENANCE

Keep the unit clean, wipe off any fluid spillage. Keep the tubes clean and clear of blockages. Check that all tubes and connections are in good condition.







ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR