

# INSTRUCTIONS FOR

# LED WORK SPOTLIGHT 12W/48W MODEL NO: WL12W, WL48W

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

**IMPORTANT:** PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



instruction

# 1. SAFETY

### 1.1. ELECTRICAL SAFETY

- WARNING! It is the responsibility of the owner and the operator to read, understand and comply with the following: You must check all electrical products, before use, to ensure that they are safe. You must inspect power cables, plugs, sockets and any other connectors for wear or damage.
- Ensure that cables are always protected against short circuit and overload.
- Regularly inspect power supply cables check all connections to ensure that none are loose.
  Important: Ensure that the voltage marked on the appliance matches the power supply to be used and that the circuit is fitted with the correct fuse. If in doubt, consult a qualified technician to connect the spotlight to a fused and switched DC supply.
- **× DO NOT** pull or carry the spotlight by the power cable.
- DO NOT use worn or damaged cables, plugs or connectors. Immediately have any faulty item repaired or replaced by a qualified technician.

## 2. INTRODUCTION

### Model No: WL12W

Spotlight with 4 x 3W Epistar™ high power LEDs producing up to 840 lumen output. IP67 Rated with a powder coated die cast aluminium housing. Suitable replacement for traditional halogen work lights with up to 80% less power consumption. Supplied with grade 304 stainless steel mounting bracket and fixings.

#### Model No: WL48W

Spotlight with 16 x 3W Epistar<sup>™</sup> high power LEDs producing up to 3450 lumen output. IP67 Rated with a powder coated die cast aluminium housing. Suitable replacement for traditional halogen work lights with up to 12% less power consumption. Supplied with grade 304 stainless steel mounting bracket and fixings.

# 3. SPECIFICATION

Model No:	
Power:	
Lumen Output:	840lm
Supply:	9-32V DC
Dimension:	Ø80mm
Model No:	WL48W
Power:	
Lumen Output:	3450lm
Supply:	9-32V DC
Dimensions:	125 x 110mm





#### **WEEE REGULATIONS**

Dispose of this product at the end of its working life in compliance with the EU Directive on Waste Electrical and Electronic Equipment (WEEE). When the product is no longer required, it must be disposed of in an environmentally protective way. Contact your local solid waste authority for recycling information.



#### **ENVIRONMENT PROTECTION**

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR