

Technical product information Protection Paper P50

Protection paper with ultra-removable adhesive

Description	
Universal cover and surface protection material based on a robust, tear-resistant kraft paper and a substrate-friendly and residue-free water based special adhesive.	
Application	
Protection Paper P50 is ideally suited for the easy and efficient protective covering in renovation work, craftsmanship or for transport protection. Due to the easy roll-off the product can be applied very quickly, even for covering large areas e.g. windowsills, radiators, handrails, furniture, etc. The substrate-friendly special adhesive allows the application on highly sensitive surfaces, such as paper wallpapers, veneers, sensitive wood surfaces or poorly adhering paints or colors.	
Application details	
Protection Paper P50 provides good protection against paint splashes, dirt and dust. The product is not suitable for direct coating with paint or varnish or while using larger amounts of water. To achieve sharp paint or varnish edges, a suitable adhesive tape should be used. The product can be removed from almost all surfaces without leaving residue and is very gentle to the substrate. Due to the large number of substrates and conditions of use in practice, a trial bonding should always be carried out in an inconspicuous place in order to check the suitability. This is especially true when applied to natural or artificial stone.	
Max. application time	60 Days 14 Days on high-sensitive surfaces (e.g. paper wallpapers)
Storage condition	10 - 30°C; 40 - 60 % rel. humidity, protected from light
storage stability @ 20°C, 50% R.H.	2 years
Technical data	
Backing material	Kraft paper natural brown
Adhesive	Special polyacrylate, waterborne, free of solvent
Thickness	65 µm
Peel adhesion	30 cN / 25 mm
Tensile strength	58 N / 15 mm