



If straight joints are formed in runs of masonry wall, the designer may either wish to form a bond or allow movement. This can be achieved using bonding or debonding strip ties.



[UK-DoP-h13/0022](#)



APPLICATIONS

Material

- Galvanised mild steel & austenitic stainless steel
- Plastic sleeve

TECHNICAL DATA

DBST Debonding Strip Tie

References	Material	Ties		Sleeve	
		L [mm]	W [mm]	L [mm]	W [mm]
DBST200G	Galvanised	200	21.5	135	25
DBST200S	Stainless Steel	200	21.5	135	25
DBST225S	Stainless Steel	225	21.5	135	25
DBST250S	Stainless Steel	250	21.5	135	25
DBST225G	-	-	-	-	-
DBST250G	-	-	-	-	-
DBST	-	-	-	-	-

DBST Product Dimensions

References	Material	Dimensions [mm]				
		A	B	t	A _{sleeve}	B _{sleeve}
DBST200G	Galvanised	21.5	200	1	25	135
DBST200S	Stainless Steel	21.5	200	1	25	135
DBST225S	Galvanised	21.5	225	1	25	135
DBST250S	Stainless Steel	21.5	225	1	25	135
DBST225G	Galvanised	21.5	250	1	25	135
DBST250G	Stainless Steel	21.5	250	1	25	135

DBST Performance Tables

References	Characteristic Capacity [N]	
	Shear	
	1mm Serviceability	Ultimate
DBST	333	959

